



WHEREVER TIRES ARE CHANGED™

AIR CHUCKS



**AUTO-GRIP AIR CHUCK
PN 25001**

Auto-grip to any style valve stem stays air-tight under pressure and includes one-button quick release. Rotates 360° for better operational flexibility.



CAUTION! Max Inflation Pressure: 200psi / 14 bar.



**EXTENDED AUTO-GRIP AIR CHUCK
WITH HANDLE PN 25004**

Innovative automatic clamping design maintains an airtight seal under high pressure.



CAUTION! Max Inflation Pressure: 200psi / 14 bar.



CAUTION! Max Inflation Pressure: 160psi / 11 bar.

Features Valve Core Installation, Valve Core Removal and Quick Tire Inflation.



**3-IN-1 INFLATOR & TIRE VALVE
CORE EXTRACTOR TOOL PN 25008**

Auto-grip to any style valve stem stays air-tight under pressure and includes one-button quick release. Used for portable inflators to screw on to the end of the hose. Rotates 360° for better operational flexibility.



CAUTION! Max Inflation Pressure: 200psi / 14 bar.



**AUTO-GRIP AIR CHUCK WITH
SCREW-ON ADAPTER PN 25010**



www.KENTOOL.com



WARNING: Cancer and Reproductive harm www.P65warnings.ca.gov

1-888-536-8665

768 E. North Street, P.O. Box 9320 | Akron, Ohio 44305 | 330-535-7177 | sales@kentool.com | © 2026 Ken-Tool. All Rights Reserved. KT2026011